4BC8

Medium-Mu Twin Triode

With Semiremote-Cutoff Characteristic

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4BC8 is the same as the 6BC8 except for the following items:

Heater Characteristics and Ratings *(Design-Center Values):*		
Current	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600	4.2	volts
Warm-up time (Average)	11	sec

4BL8

Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4BL8 is the same as the 6BL8 except for the following items:

Heater Characteristics and Ratings *(Design-Center Values):*		
Current	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600	4.6	volts

4BN6

Beam Tube

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4BN6 is the same as the 6BN6 except for the following items:

Heater Characteristics and Ratings *(Design-Maximum Values):*		
Current	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450	4.2	volts
Warm-up time (Average)	11	sec