8CG7

Medium-Mu Twin Triode

CONTROLLED HEATER WARM-UP TIME

The 8CG7 is the same as the 6CG7 except for the following items:

Heater Characteristics and Ratings:

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp	8.4	volts

8CM7

Medium-Mu Dual Triode

With Dissimilar Units

CONTROLLED HEATER WARM-UP TIME

The 8CM7 is the same as the 6CM7 except for the following items:

Heater Characteristics and Ratings:

Current	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp	8.4	volts

8CN7

Twin Diode—High-Mu Triode

CONTROLLED HEATER WARM-UP TIME

The 8CN7 is the same as the 6CN7 except for the following items:

Heater Characteristics and Ratings:

Heater-section arrangement	*Parallel*	*Series*	*Series*	
Voltage (AC or DC)	4.2[a]	8.4[b]	8.4 ± 0.8	volts
Current	0.450 ± 0.030	0.225 ± 0.010	0.225[c]	amp

[a] At 0.450 ampere.
[b] At 0.225 ampere.
[c] At 8.4 volts.

RADIO CORPORATION OF AMERICA
Electronic Components and Devices Harrison, N. J.

DATA
5-65